

DOOR TYPE DISHWASHER

STANDARD

POWER

POWERFUL washing standards. Sustained pressure to deliver extraordinary results. Selectable wash timing. Stainless steel impellers housing.



DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. **ENDURING** performance with zero-trouble experience.



DYNAMIC

Electrical components are not affected by the different environment and kitchen settings it is put into. It delivers **CONSISTENT** results everywhere.



GT-D1M (TC-RB)

TECHNICAL DATA

Model:	GT-D1M (LE-RB) / GT-D1M (TC-RB)
Dimensions (mm):	697 (W) x 690 (D) x 1585 (H)
Loading height (mm):	420
Rack type (mm):	500 x 500
Machine net weight	128 kg

ELECTRICAL POWER LOADING

Voltage:	220V ~ 240V 50Hz 1 Phase	380V ~ 415V 50Hz 3 Phase
	220V ~ 230V 60Hz 1 Phase [PH models]	220V ~ 230V 60Hz 3 Phase [PH models]
Electrical loading:	3.5 kW 15 A (Alternative Heating)	11 kW 15 A (Alternative Heating)
	-	14 kW 20 A (Full Heating)
	3.5 kW 24 A (Alternative Heating) [PH models]	11 kW 36 A (Alternative Heating) [PH models]
Wash tank heater:	2 kW	3 kW
Booster tank heater:	2 kW	9 kW
Wash pump:	0.95 kW	
Rinse pump:	0.25 kW	

OPERATING INFORMATION

Wash temperature:	55°C - 65°C
Rinse temperature:	82°C - 90°C
Wash cycle (per rack):	60/90 sec
	70/100 sec *(LE-RB)
Wash rate (per hour):	60/40 racks
	50/36 racks *(LE-RB)
Rinse usage:	<2 liters per cycle
Wash tank capacity:	36 liters
Booster tank capacity:	10 liters
Chemical dispensers:	NA
Automated Drain pump:	NA

