

# HOOD TYPE DISHWASHER

## STANDARD



GT-D1H

### POWER

Powerful washing standards. Sustained pressure to deliver extraordinary results. Selectable wash timing. Stainless steel impellers housing.



### DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. **ENDURING** performance with zero-trouble experience.



### DIGITAL

Digital displays and minimum cluttering provides a user-friendly experience. Simple usability and reliable components.



## TECHNICAL DATA

|                             |                                 |
|-----------------------------|---------------------------------|
| <b>Model:</b>               | GT-D1H 1 Phase / GT-D1H 3 Phase |
| <b>Dimensions (mm):</b>     | 697 (W) x 691 (D) x 1447 (H)    |
| <b>Loading height (mm):</b> | 420                             |
| <b>Rack type (mm):</b>      | 500 x 500                       |
| <b>Machine net weight</b>   | 122 kg                          |

### ELECTRICAL POWER LOADING

|                             |                                                        |                                                       |
|-----------------------------|--------------------------------------------------------|-------------------------------------------------------|
| <b>Voltage:</b>             | 220V ~ 240V   50Hz   1 Phase                           | 380V ~ 415V   50Hz   3 Phase                          |
|                             | 220V ~ 230V   60Hz   1 Phase <b>[PH models]</b>        | 220V ~ 230V   60Hz   3 Phase <b>[PH models]</b>       |
| <b>Electrical loading:</b>  | 3.5 kW   15 A (Alternative Heating)                    | 11 kW   15 A (Alternative Heating)                    |
|                             | -                                                      | 14 kW   20 A (Full Heating)                           |
|                             | 3.5 kW   24 A (Alternative Heating) <b>[PH models]</b> | 11 kW   36 A (Alternative Heating) <b>[PH models]</b> |
| <b>Wash tank heater:</b>    | 2 kW                                                   | 3 kW                                                  |
| <b>Booster tank heater:</b> | 2 kW                                                   | 9 kW                                                  |
| <b>Wash pump:</b>           | 0.95 kW                                                |                                                       |
| <b>Rinse pump:</b>          | 0.25 kW                                                |                                                       |

### OPERATING INFORMATION

|                               |                                       |
|-------------------------------|---------------------------------------|
| <b>Wash temperature:</b>      | 55°C - 65°C                           |
| <b>Rinse temperature:</b>     | 82°C - 90°C                           |
| <b>Wash cycle (per rack):</b> | 60/90 sec<br>70/90 sec *(1 Phase)     |
| <b>Wash rate (per hour):</b>  | 60/45 racks<br>50/36 racks *(1 Phase) |
| <b>Rinse usage:</b>           | <2 liters per cycle                   |
| <b>Wash tank capacity:</b>    | 36 liters                             |
| <b>Booster tank capacity:</b> | 10 liters                             |
| <b>Chemical dispensers:</b>   | NA                                    |
| <b>Automated Drain pump:</b>  | NA                                    |

