

GT-UW/S UTENSIL WASHER

THE ALL-IN-ONE WASHING EXPERIENCE



POWER

SUPERIOR washing results. Sustained pressure powered by at 3HP / 2.4kW motor through 4 upper & 4 lower stainless steel wash arms.



DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. ENDURING performance with zero-trouble experience.



SPACE

Large loading SPACE allowing high washing capacity and high output. Time-saving factor in the kitchen proven critical.



DYNAMIC

Different rack designs to serve multiple types of washware. DYNAMIC design is exactly just what the kitchen needs.

TECHNICAL DATA

Model:	GT-UW/S
Dimensions (mm):	760 (W) x 760 (D) x 1825 (H)
Loading dimensions (mm):	550 (W) x 550 (D) x 710 (H)
Machine net weight	206 kg

OPERATING INFORMATION

Wash temperature:	55°C - 65°C
Rinse temperature:	82°C - 90°C
Wash cycle (per rack):	3 mins or 6 mins (<i>selectable</i>)
Wash rate (per hour):	20 racks or 10 racks
Rinse usage:	<2.7 liters per rack
Wash tank capacity	45.0 liters
Booster tank capacity	16.0 liters
Heating mode:	Electric

ELECTRICAL SPECIFICATIONS

Voltage supply	Booster tank	Wash tank	Wash pump	Rinse motor	Total power loading
380V - 415V, 50/60Hz, 3 Phase	9.0 kW	9.0 kW	2.4 kW (3 HP)	0.15 kW	14.6 kW, 22.6 A (<i>Alternative Heating</i>) 22.2 kW, 36.5 A (<i>Full Heating</i>)
220V - 240V, 60Hz, 3 Phase	9.0 kW	9.0 kW	2.4 kW (3 HP)	0.15 kW	14.6 kW, 42.7 A (<i>Alternative Heating</i>) 23.6 kW, 69.1 A (<i>Full Heating</i>)

